

TAA CAT 5E EASY CLEAR BOOT ETHERNET CABLES



The CAT 5E easy clear boot PVC ethernet cable from ProLabs is a high-quality, reliable patch cable designed for demanding networking environments. This cable features RJ-45 (male) to RJ-45 (male) connectors with a low profile easy boot locking tab protector. The cable remains lightweight and flexible, making it easier to run with fewer snags.

Features

- **High-Speed Connectivity:** The CAT 5E cable supports data transfer speeds of up to 1Gbps (Gigabit per second), and operates at a frequency of up to 100MHz with a range of up to 100 meters (328 feet). This makes it suitable for a variety of networking tasks, from simple internet browsing to more demanding applications like video streaming and online gaming.
- **Unshielded Twisted Pair (UTP):** The cable consists of pairs of insulated copper wires twisted together. This design helps to minimize electromagnetic interference (EMI) and crosstalk between pairs, ensuring a stable and reliable connection.
- **PVC-CM Jacket:** The cable is encased in a durable PVC-CM jacket, which is suitable for indoor use. This type of jacket is flexible and lightweight, making the cable easy to manage and install.
- **PoE Capable:** The cable supports Power over Ethernet (PoE), allowing it to transmit both data and power over a single cable. This is particularly useful for devices like IP cameras, VoIP phones, and wireless access points.
- **TIA Compliant:** The cable meets the standards set by the Telecommunications Industry Association (TIA), ensuring it performs reliably for all networking needs.
- **TAA Compliant:** The cable meets the standards set by the Trade Agreement Act (TAA).



Part Number Template


Color	Lengths
Red	C-xFCAT5E-RD-TAA
Orange	C-xFCAT5E-OE-TAA
Yellow	C-xFCAT5E-YW-TAA
Green	C-xFCAT5E-GN-TAA
Blue	C-xFCAT5E-BE-TAA
Purple	C-xFCAT5E-PE-TAA
Black	C-xFCAT5E-BK-TAA
Gray	C-xFCAT5E-GY-TAA
White	C-xFCAT5E-WE-TAA

Technical Specifications


Parameter	Specification
Boot Type:	Easy Clear Boot
Connector Type:	RJ-45 (Male) to RJ-45 (Male)
Wire Gauge:	24AWG
Conductor Material:	Copper
Termination Type:	Straight
Shielding:	None (UTP)
Strain Relief:	Yes
Wire Scheme:	T568B

For a full list of products, please visit us at prolabs.com/copper

Mechanical Specifications



	1		8
Color (T568B)	P1	Pairs	P2
WHITE/ORANGE	1	-----	1
ORANGE	2	-----	2
WHITE/GREEN	3	-----	3
BLUE	4	-----	4
WHITE/BLUE	5	-----	5
GREEN	6	-----	6
WHITE/BROWN	7	-----	7
BROWN	8	-----	8



Length	Tolerance
L<1M	+/-30mm
1M<L<5M	+/-50mm
5M<L<10M	+/-100mm
L>10M	+/-150mm

ProLabs is a leading provider of optical networking solutions. For over two decades, we have delivered optical connectivity solutions that give customers freedom, choice, and seamless interoperability. We serve a diverse range of industries including enterprises, governments, and the largest worldwide service providers.

By championing higher standards for technology and service, ProLabs is changing the mindset of data centers and service providers the world over. We supply solutions that are 100% compatible in form and functionality across 100 OEM manufacturers, covering more than 20,000 systems and platforms.



North America

sales@prolabs.com
+1 952 852 0252

EMEA

salesemea@prolabs.com
+44 1285 719 600

For more information, please visit www.prolabs.com

