

SLIM CAT 5E CLEAR-CLAW ETHERNET CABLES



Engineered for precision and performance, the slim CAT 5E clear-claw PVC ethernet cable from ProLabs combines durability with a sleek, space-saving design. Featuring transparent RJ-45 (male) to RJ-45 (male) connectors, this high-quality patch cable offers both reliability and visual clarity, ideal for high-density networking setups where organization and signal integrity matter most.

Features

- **High-Speed Connectivity:** The CAT 5E cable supports data transfer speeds of up to 1Gbps (Gigabit per second), and operates at a frequency of up to 100MHz with a range of up to 100 meters (328 feet). This makes it suitable for a variety of networking tasks, from simple internet browsing to more demanding applications like video streaming and online gaming.
- **Unshielded Twisted Pair (UTP):** The cable consists of pairs of insulated copper wires twisted together. This design helps to minimize electromagnetic interference (EMI) and crosstalk between pairs, ensuring a stable and reliable connection.
- **PVC-CM Jacket:** The cable is encased in a durable PVC-CM jacket, which is suitable for indoor use. This type of jacket is flexible and lightweight, making the cable easy to manage and install.
- **PoE Capable:** The cable supports Power over Ethernet (PoE), allowing it to transmit both data and power over a single cable. This is particularly useful for devices like IP cameras, VoIP phones, and wireless access points.
- **TIA Compliant:** The cable meets the standards set by the Telecommunications Industry Association (TIA), ensuring it performs reliably for all networking needs.



Part Number Template


Color	Lengths
Red	C-xFSLCAT5E-RD
Orange	C-xFSLCAT5E-OE
Yellow	C-xFSLCAT5E-YW
Green	C-xFSLCAT5E-GN
Blue	C-xFSLCAT5E-BE
Purple	C-xFSLCAT5E-PE
Black	C-xFSLCAT5E-BK
Gray	C-xFSLCAT5E-GY
White	C-xFSLCAT5E-WE

Technical Specifications

Parameter	Specification
Boot Type:	Clear-Claw
Connector Type:	RJ-45 (Male) to RJ-45 (Male)
Wire Gauge:	28AWG
Conductor Material:	Copper
Termination Type:	Straight
Shielding:	None (UTP)
Strain Relief:	Yes
Wire Scheme:	T568B

For a full list of products, please visit us at prolabs.com/copper

Mechanical Specifications



			
Color (T568B)	P1	Pairs	P2
WHITE/ORANGE	1	-----	1
ORANGE	2	-----	2
WHITE/GREEN	3	-----	3
BLUE	4	-----	4
WHITE/BLUE	5	-----	5
GREEN	6	-----	6
WHITE/BROWN	7	-----	7
BROWN	8	-----	8

Copper Conductor

Rip Cord

Twisted Pairs

Spline

Insulator

Jacket

Length	Tolerance
L<1M	+/-30mm
1M<L<5M	+/-50mm
5M<L<10M	+/-100mm
L>10M	+/-150mm

ProLabs is a leading provider of optical networking solutions. For over two decades, we have delivered optical connectivity solutions that give customers freedom, choice, and seamless interoperability. We serve a diverse range of industries including enterprises, governments, and the largest worldwide service providers.

By championing higher standards for technology and service, ProLabs is changing the mindset of data centers and service providers the world over. We supply solutions that are 100% compatible in form and functionality across 100 OEM manufacturers, covering more than 20,000 systems and platforms.



North America

sales@prolabs.com
+1 952 852 0252

EMEA

salesemea@prolabs.com
+44 1285 719 600

For more information, please visit www.prolabs.com

