

FC95734AAX-C

Fujitsu® FC95734AAX Compatible TAA 10GBase-DWDM 50GHz XFP Transceiver (SMF, 1530nm to 1565nm, 80km, LC)

Features:

- INF-8077i Compliance
- Duplex LC Connector
- Single-mode Fiber
- Commercial Temperature 0 to 70 Celsius
- Hot Pluggable
- Metal with Lower EMI
- Excellent ESD Protection
- RoHS Compliant and Lead Free



Applications:

- 10x Gigabit Ethernet over DWDM
- 8x/10x Fibre Channel
- Access, Metro and Enterprise

Product Description

This Fujitsu® FC95734AAX compatible XFP transceiver provides 10GBase-DWDM throughput up to 80km over single-mode fiber (SMF) using a wavelength of 1530nm to 1565nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent Fujitsu® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. It is built to meet or exceed the specifications of Fujitsu®, as well as to comply with MSA (Multi-Source Agreement) standards to ensure seamless network integration. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

ProLabs's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S. – made or designated country end products."



Regulatory Compliance

- ESD to the Electrical PINs: compatible with MIL-STD-883E Method 3015.4
- ESD to the LC Receptacle: compatible with IEC 61000-4-3
- EMI/EMC compatible with FCC Part 15 Subpart B Rules, EN55022:2010
- Laser Eye Safety compatible with FDA 21CFR, EN60950-1& EN (IEC) 60825-1,2
- RoHS compliant with EU RoHS 2.0 directive 2015/863/EU

Tunable XFP Channel Number and Wavelength

| Channel No. | Frequency (THz) | Center Wavelength | Channel No. | Frequency (THz) | Center Wavelength |
|-------------|-----------------|-------------------|-------------|-----------------|-------------------|
| 1 | 191.35 | 1566.723 | 49 | 193.75 | 1547.316 |
| 2 | 191.40 | 1566.314 | 50 | 193.80 | 1546.917 |
| 3 | 191.45 | 1565.905 | 51 | 193.85 | 1546.518 |
| 4 | 191.50 | 1565.496 | 52 | 193.90 | 1546.119 |
| 5 | 191.55 | 1565.087 | 53 | 193.95 | 1545.720 |
| 6 | 191.60 | 1564.679 | 54 | 194.00 | 1545.322 |
| 7 | 191.65 | 1564.271 | 55 | 194.05 | 1544.924 |
| 8 | 191.70 | 1563.863 | 56 | 194.10 | 1544.526 |
| 9 | 191.75 | 1563.455 | 57 | 194.15 | 1544.128 |
| 10 | 191.80 | 1563.047 | 58 | 194.20 | 1543.730 |
| 11 | 191.85 | 1562.640 | 59 | 194.25 | 1543.333 |
| 12 | 191.90 | 1562.233 | 60 | 194.30 | 1542.936 |
| 13 | 191.95 | 1561.826 | 61 | 194.35 | 1542.539 |
| 14 | 192.00 | 1561.419 | 62 | 194.40 | 1542.142 |
| 15 | 192.05 | 1561.013 | 63 | 194.45 | 1541.746 |
| 16 | 192.10 | 1560.606 | 64 | 194.50 | 1541.349 |
| 17 | 192.15 | 1560.200 | 65 | 194.55 | 1540.953 |
| 18 | 192.20 | 1559.794 | 66 | 194.60 | 1540.557 |
| 19 | 192.25 | 1559.389 | 67 | 194.65 | 1540.162 |
| 20 | 192.30 | 1558.983 | 68 | 194.70 | 1539.766 |
| 21 | 192.35 | 1558.578 | 69 | 194.75 | 1539.371 |
| 22 | 192.40 | 1558.173 | 70 | 194.80 | 1538.976 |
| 23 | 192.45 | 1557.768 | 71 | 194.85 | 1538.581 |
| 24 | 192.50 | 1557.363 | 72 | 194.90 | 1538.186 |
| 25 | 192.55 | 1556.959 | 73 | 194.95 | 1537.792 |
| 26 | 192.60 | 1556.555 | 74 | 195.00 | 1537.397 |
| 27 | 192.65 | 1556.151 | 75 | 195.05 | 1537.003 |

| | | | | | |
|-----------|--------|----------|-----------|--------|----------|
| 28 | 192.70 | 1555.747 | 76 | 195.10 | 1536.609 |
| 29 | 192.75 | 1555.343 | 77 | 195.15 | 1536.216 |
| 30 | 192.80 | 1554.940 | 78 | 195.20 | 1535.822 |
| 31 | 192.85 | 1554.537 | 79 | 195.25 | 1535.429 |
| 32 | 192.90 | 1554.134 | 80 | 195.30 | 1535.036 |
| 33 | 192.95 | 1553.731 | 81 | 195.35 | 1534.643 |
| 34 | 193.00 | 1553.329 | 82 | 195.40 | 1534.250 |
| 35 | 193.05 | 1552.926 | 83 | 195.45 | 1533.858 |
| 36 | 193.10 | 1552.524 | 84 | 195.50 | 1533.465 |
| 37 | 193.15 | 1552.122 | 85 | 195.55 | 1533.073 |
| 38 | 193.20 | 1551.721 | 86 | 195.60 | 1532.681 |
| 39 | 193.25 | 1551.319 | 87 | 195.65 | 1532.290 |
| 40 | 193.30 | 1550.918 | 88 | 195.70 | 1531.898 |
| 41 | 193.35 | 1550.517 | 89 | 195.75 | 1531.507 |
| 42 | 193.40 | 1550.116 | 90 | 195.80 | 1531.116 |
| 43 | 193.45 | 1549.715 | 91 | 195.85 | 1530.725 |
| 44 | 193.50 | 1549.315 | 92 | 195.90 | 1530.334 |
| 45 | 193.55 | 1548.915 | 93 | 195.95 | 1529.944 |
| 46 | 193.60 | 1548.515 | 94 | 196.00 | 1529.553 |
| 47 | 193.65 | 1548.115 | 95 | 196.05 | 1529.163 |
| 48 | 193.70 | 1547.715 | 96 | 196.10 | 1528.773 |

Absolute Maximum Ratings

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Notes |
|------------------------------|--------|------|------|------|------|---------------------|
| Storage Temperature | Tstg | -40 | | 85 | °C | |
| Case Temperature | | -5 | | 70 | °C | |
| ESD | | 500 | | | V | High Speed i/o pins |
| | | 2000 | | | | All other pins |
| Receiver optical input power | | | | +12 | dBm | |

Electrical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Notes |
|-------------------------|--------|------|------|------|-------|----------------------------------|
| 1.8V Supply | Vcc2 | 1.71 | 1.8 | 1.89 | V | VPS not supported |
| 3.3V Supply | Vcc3 | 3.15 | 3.3 | 3.45 | V | |
| 5.0V Supply | Vcc5 | 4.75 | 5.0 | 5.25 | V | |
| Supply Current, 1.8V | | | 160 | 200 | mA | |
| Supply Current, 3.3V | | | 310 | 400 | mA | |
| Supply Current, 5.0V | | | 100 | 200 | mA | |
| Inrush current limit | | | | 100 | mA/μs | |
| Total power consumption | | | | 2.5 | W | Power Level 2 MSA classification |

System Performance

| Parameter | Min | Max | OSNR | BER | Conditions |
|-------------------|-----------|-----------|-------|-------|---|
| Noise Loaded | -400ps/nm | 1500ps/nm | 19dB | 1E-04 | 10.709Gb/s, -10 to -20dBm, 0.25nm filter, optimised RxDTV |
| Unamplified Links | 0ps/nm | 1600ps/nm | >35dB | 1E-12 | 10.709Gb/s, -22dBm, 0.25nm filter, optimised RxDTV |

Optical Characteristics


| Parameter | Symbol | Min. | Typ. | Max. | Unit | Conditions |
|--------------------------------|---------------------|--------|------|--------|---------|--|
| Transmitter | | | | | | |
| Data Rate | | 9.95 | | 11.35 | Gb/s | NRZ |
| Frequency range | | 191.35 | | 196.10 | THz | 50GHz grid, 96 channels |
| Frequency accuracy | | -2.5 | | +2.5 | GHz | EOL |
| Optical transmit power | Po | | +0.5 | | dBm | SOL, 25°C |
| Optical transmit power | Po | -1 | | +3.0 | dBm | EOL |
| Shuttered output power | | | -45 | -40 | dBm | |
| Optical power stability | ΔP_{out} | -1.0 | | +1.0 | dB | All channels, SOL |
| Side mode suppression | SMSR | 35 | | | dB | ± 2.5 nm, modulated |
| Spectral width | $\Delta\lambda$ | | 0.3 | 0.5 | nm | -20dB, modulated |
| Extinction ratio | ER | 9.5 | | | dB | Filtered, 10.709Gb/s |
| Eye diagram compliance | GR-253, ITU-T G.691 | | | | | |
| Mask margin | | 10 | | | % | |
| OSNR | | 50 | 55 | | dB | 0.1nm RBW |
| SBS threshold | | 18 | | | dBm | 50km SMF |
| Tuning speed | | | | 50 | ms | |
| Laser enable (turn on) time | | | | 50 | ms | To >90% power |
| Laser disable (turn off) time | | | | 10 | μ s | To <10% power |
| Module initialization time | | | | 20 | s | |
| Receiver | | | | | | |
| Data rate | | 9.95 | | 11.35 | Gb/s | NRZ |
| Input operating wavelength | λ | 1525 | | 1575 | nm | |
| Receiver Sensitivity | | | -26 | | dBm | 10.709 Gb/s, IE-12, OSNR>35dB, optimized RxDTV |
| Maximum input power (overload) | Pin MAX | -5 | | | dBm | |
| LOS assert | PA | -33 | | -28.5 | dBm | |
| LOS de-assert | PD | -32.5 | | -26.5 | dBm | |
| LOS Hysteresis | PD - PA | 0.5 | | 4 | dB | |
| LOS assert time | TA | | | 100 | μ s | |
| LOS de-assert time | TD | | | 100 | μ s | |

Pin Descriptions


| Pin | Logic | Symbol | Name/Descriptions | Notes |
|-----|-----------|------------|--|-------|
| 1 | | GND | Module Ground | 1 |
| 2 | | VEE5 | Optional -5.2V Power Supply | |
| 3 | LVTTL-I | Mod-Desel | Module De-select, when held low allows the module to respond to 2-wire serial interface commands | |
| 4 | LVTTL-O | Interrupt | Interrupt; Indicates presence of an important condition which can be read over the serial 2-wire interface | 2 |
| 5 | LVTTL-I | TX_DIS | Transmitter Disable; Turns off transmitter laser output | |
| 6 | | VCC5 | +5V Power Supply | |
| 7 | | GND | Module Ground | 1 |
| 8 | | VCC3 | +3.3V Power Supply | |
| 9 | | VCC3 | +3.3V Power Supply | |
| 10 | LVTTL-I/O | SCL | 2-wire Serial interface clock | 2 |
| 11 | LVTTL-I/O | SDA | 2-wire Serial interface data line | 2 |
| 12 | LVTTL-O | Mod_Abs | Indicates Module is not present. Grounded in the Module | 2 |
| 13 | LVTTL-O | Mod_NR | Module Not Ready; Indicating Module Operational Fault | 2 |
| 14 | LVTTL-O | RX_LOS | Receiver Loss Of Signal Indicator | 2 |
| 15 | | GND | Module Ground | 1 |
| 16 | | GND | Module Ground | 1 |
| 17 | CML-O | RD- | Receiver Inverted Data Output | |
| 18 | CML-O | RD+ | Receiver Non-Inverted Data Output | |
| 19 | | GND | Module Ground | 1 |
| 20 | | VCC2 | +1.8V Power Supply | 3 |
| 21 | LVTTL-I | P Down/RST | Power down; When high, requires the module to limit power consumption to 1.5W or below. 2-Wire serial interface must be functional in the low power mode. Reset; The falling edge initiates a complete reset of the module including the 2-wire serial interface, equivalent to a power cycle | |
| 22 | | VCC2 | +1.8V Power Supply | 3 |
| 23 | | GND | Module Ground | 1 |
| 24 | PECL-I | RefCLK+ | Not required | |
| 25 | PECL-I | RefCLK- | Not required | |
| 26 | | GND | Module Ground | 1 |
| 27 | | GND | Module Ground | 1 |
| 28 | CML-I | TD- | Transmitter Inverted Data Input | |
| 29 | CML-I | TD+ | Transmitter Non-Inverted Data Input | |
| 30 | | GND | Module Ground | 1 |

Notes:

1. Module ground pins (GND) are isolated from the module case and chassis ground within the module.
2. Shall be pulled up with 4.7K-10kOhms to a voltage between 3.15V and 3.45V on the host board.
3. Variable Power Supply (VPS) function is not supported.



Recommended Pattern Layout



Power Supply Noise Tolerance





Figure 2 Power Noise Requirement

Mechanical Specifications



About ProLabs

Our experience comes as standard; for over 15 years ProLabs has delivered optical connectivity solutions that give our customers freedom and choice through our ability to provide seamless interoperability. At the heart of our company is the ability to provide state-of-the-art optical transport and connectivity solutions that are compatible with over 90 optical switching and transport platforms.

Complete Portfolio of Network Solutions

ProLabs is focused on innovations in optical transport and connectivity. The combination of our knowledge of optics and networking equipment enables ProLabs to be your single source for optical transport and connectivity solutions from 100Mb to 400G while providing innovative solutions that increase network efficiency. We provide the optical connectivity expertise that is compatible with and enhances your switching and transport equipment.

Trusted Partner

Customer service is our number one value. ProLabs has invested in people, labs and manufacturing capacity to ensure that you get immediate answers to your questions and compatible product when needed. With Engineering and Manufacturing offices in the U.K. and U.S. augmented by field offices throughout the U.S., U.K. and Asia, ProLabs is able to be our customers best advocate 24 hours a day.

Contact Information

ProLabs US

Email: sales@prolabs.com

Telephone: 952-852-0252

ProLabs UK

Email: salessupport@prolabs.com

Telephone: +44 1285 719 600